



CCV Edge IM25

Android unattended self-service payment terminal for contactless payments



PIN on glass | prevents consumers from 'can't pay situations' as it enables contactless payments with PIN on demand



Compact | the all-capabilities terminal design fits even into small machines and into standard cut-outs



Adaptable | terminal can be installed flexibly, in landscape or portrait format



Connectivity | it connects anywhere with its multiple built-in interfaces and optional 4G interface for remote locations



Display	3.5" TFT LCD 480 x 320 Touch Screen 600 nits Supports PIN on Glass front-glass hardness 6 Mohs
Card Readers	Contact Card, Magnetic stripe: via external optional IM500
Scanner	Reads 1D & 2D codes
Keys / buttons	1 x Reset key (rear)
Audio	1 x Speaker (side)
Dimensions	108,4 x 75 x 43mm (W x H x D) 108,4 x 75 x 18,5mm (W x H x D) outside the machine, 72 x 60 x 24,5mm (W x H x D) within the machine (without cables and mounting accessories)
Front plane cut-out	73 x 61mm (W x H), EVA EPS 2.1 CDM compliant Front mounting
Connectivity	1 x USB Host (USB-A) 1 x USB Device (USB-C) 1 x LAN 1 x RS232 1 x MDB WiFi 2,4 / 5GHz Bluetooth 5.0 max. baudrate 115200 4G RF Modem (optional)
Digital I/O	1x WAGO 6-pin 733-106 (rear)
Power supply	7 - 48 VDC via main power supply, MDB, or RS232 (12 to 48VDC)
Power consumption (Without IM500)	Without 4G modem @ 12 VDC: max 500 mA 130 mA standby 5mA sleep With 4G modem @ 12 VDC: max 1.5 A 100 mA standby 8 mA sleep
Security	2x Secure Access Module (SAM) slots
Environmental	-20°C ~ 70°C (-4°F ~ 158°F) Operating Temperature -30°C ~ 70°C (-22°F ~ 158°F) Storage Temperature 5% ~ 95% Relative Humidity, Non Condensing IP 65 IK09
Flammability rating	V2 according to UL94, IEC 60695-11-10, -20 and IEC 60950-1
Certifications	Payment: EMV Contactless L1 Mastercard PayPass L2 Visa payWave L2 American ExpressPay L2 Discover D-PAS L2 Interac_Flash L2 J/Speedy L2 Mastercard TQM qPBOC L1 qUICS L2 DK TA 7.2 Security: PCI PTS 6.x, SRED CSEC UKCC DC POS 3.0 CTAP 11 Regulatory: FCC IC UL RoHS CE UKCA

All specifications are subject to change and are to be confirmed in the course of the qualification process.