

let's make
payment
happen




CCV Pad Next

High performance
PIN-Pad

- Large display for easy signature capture
- Front camera (prepared) for reading QR codes / barcodes
- Detached, illuminated contactless reader for user-friendly payment



CCV Pad Next | Technical data



Software functionalities from CCV (Extract)

- Large number of supported bonus cards (e.g. Miles & More, SIXT)
- DCC Currency Conversion & TaxFree (implementation of EU Directive 2019/518, large currency flags)
- E-Receipt solution: Receipt by email to customer and/or dealer email (via QR Code Scan)
- Full OmniChannel functionality through interface to eCommerce systems
- AliPay and WeChat Pay acceptance
- P2PE Certification
- 17 languages, currencies and time zones available

Display	4" colour display 800 x 480 Pixel (WVGA) Capacitive touchscreen Integrated signature pad	
RAM	512 MB SDRAM, 512 MB Flash (expandable up to 32 GB by micro SD)	
Processor	32-bit Cortex A9, 1000 MHz	
Dimension	199 x 112 x 53,1 mm Weight: 400 g	
Keypad	Backlit, tactile keyboard EBS-100 compliant, 10 numeric keys, 3 function keys, 1 reset button	
Audio	Speaker	
External power supply	Input: 100 ~ 240V AC, 50/60Hz Output: 5V DC, 1A	
Communication/ Interface	LAN, WiFi (2,4 GHz + 5 GHz), RS232, USB, Bluetooth (incl. Beacon Technology), 3 SAM	
Card reader	Contactless reader: ISO 14443 A/B, MIFARE, girocard contactless, Mastercard contactless, Visa contactless, American Express contactless, Diners contactless, UPI contactless Chip card reader: EMV L1 & L2 Magnetic stripe reader: 3 track, bidirectional Camera (prepared) : e.g. for reading 1D & 2D codes	
Ambient conditions	Operating temp.: 0°C – 50°C Storage temp.: -20°C – 70°C	5% - 95% relative air humidity, non-condensing
Cash register protocol	ZVT, O.P.I.	
Certifications	Compatible with the current specifications DK TA7.1/DC-POS 2.5, DK TA7.2/DC POS 3.0, EMV, RoHS, CE, PCI PTS 5.x, P2PE (on request)	

Would you like to know more?
We are only one phone call **+49 8752 864 0**
or a mail sales.de@ccv.eu away

