



# CCV Frame IM25

Unattended self-service payment terminal for contactless payments



**PIN on glass** | prevents consumers from 'can't pay situations' as it enables contactless payments with PIN on demand



**Compact** | the all-capabilities terminal design fits even into small machines and into standard cut-outs



**Adaptable** | terminal can be installed flexibly, in landscape or portrait format



**Connectivity** | it connects anywhere with its multiple built-in interfaces and optional 4G interface for remote locations



Display	3.5" TFT LCD 480 x 320 Touch Screen   600 nits   Supports PIN on Glass   front-glass hardness 6 Mohs
Card Readers	Contact Card, Magnetic stripe: via external optional IM500
Scanner	Contact Card, Magnetic stripe: via external optional IM500
Keys / buttons	1 x Reset key (rear)
Audio	1 x Speaker (side)
Front plane cut-out	86.4 x 108.7(W x H), EVA EPS 2.1 compliant
Connectivity	1 x USB Host (USB-A)   1 x USB Device (USB-C)   1 x LAN   1 x RS232   1 x MDB WiFi 2,4 / 5GHz   Bluetooth 5.0 4G RF Modem (optional)
Power supply	7 - 48 VDC via main power supply, MDB, or RS232
Security	2x Secure Access Module (SAM) slots
Environmental	-20°C ~ 70°C (-4°F ~ 158°F) Operating Temperature -30°C ~ 70°C (-22°F ~ 158°F) Storage Temperature 5% ~ 95% Relative Humidity, Non Condensing IP 65   IK09
Flammability rating	V0 according to UL94, IEC 60695-11-10, -20 and IEC 60950-1
Certifications	<b>Payment:</b> EMV Contactless L1   Mastercard PayPass L2   Visa payWave L2   American ExpressPay L2   Discover D-PAS L2   Interac_Flash L2   J/Speedy L2   Mastercard TQM   qPBOC L1   qUICS L2   DK TA 7.2 <b>Security:</b> PCI PTS 6.x, SRED   CSEC   UKCC   DC POS 3.0 <b>Regulatory:</b> FCC   IC   UL   RoHS   CE   UKCA

All specifications are subject to change and are to be confirmed in the course of the qualification process.