

## CCV Frame IM25

Android unattended selfservice payment terminal for contactless payments

/

PIN on glass | prevents consumers from 'can't pay situations' as it enables contactless payments with PIN on demand

/

Compact | the all-capabilities terminal design fits even into small machines and into standard cut-outs

Adaptable | terminal can be installed flexibly, in landscape or portrait format

Connectivity | it connects anywhere with its multiple built-in interfaces and optional 4G interface for remote locations



## **Technical Data**

Display	3.5" TFT LCD 480 x 320 Touch Screen   600 nits   Supports PIN on Glass   front-glass hardness 6 Mohs
Card Readers	Contact Card, Magnetic stripe: via external optional IM500
Scanner	Reads 1D & 2D codes
Keys / buttons	1 x Reset key (rear)
Audio	1 x Speaker (side)
Front plane cut-out	86.6 x 108.9 (W x H), EVA EPS 2.1 compliant
Dimensions	99.96 x 131.96 x 43 (W x H x D) 99.96 x 131.96 x 8.18 (W x H x D) outside the machine 72 x 60 x 43mm (W x H x D) within the machine (without cables and mounting accessories)
Connectivity	1 x USB Host (USB-A)   1 x USB Device (USB-C)   1 x LAN   1 x RS232   1 x MDB WiFi 2,4 / 5GHz   Bluetooth 5.0   max. baudrate 115200 4G RF Modem (optional)
Power supply	7 - 48 VDC via main power supply, MDB, or RS232
Power consumption (without IM500)	Without 4G modem @ 12 VDC: max 500 mA   130 mA standby   5mA sleep With 4G modem @ 12 VDC: max 1.5 A   100 mA standby   8 mA sleep
Security	2x Secure Access Module (SAM) slots
Environmental	-20°C ~ 70°C (-4°F ~ 158°F) Operating Temperature -30°C ~ 70°C (-22°F ~ 158°F) Storage Temperature 5% ~ 95% Relative Humidity, Non Condensing IP 65   IK09
Flammability rating	V0 according to UL94, IEC 60695-11-10, -20 and IEC 60950-1
Certifications	Payment: EMV Contactless L1   Mastercard PayPass L2   Visa payWave L2   American ExpressPay L2   Discover D-PAS L2   Interac_Flash L2   J/Speedy L2   Mastercard TQM   qPBOC L1   qUICS L2   DK TA 7.2 Security: PCI PTS 6.x, SRED   CSEC   UKCC   DC POS 3.0   CTAP 11 Regulatory: FCC   IC   UL   RoHS   CE   UKCA

All specifications are subject to change and are to be confirmed in the course of the qualification process.

