



# CCV Pad Next

High performance PIN-Pad



**Large display for easy signature capture**



**Front camera (prepared) for reading  
QR codes / barcodes**



**Detached, illuminated contactless reader for  
user-friendly payment**



### Software functionalities from CCV (Extract)

- Large number of supported bonus cards (e.g. Miles & More, SIXT)
- DCC Currency Conversion & TaxFree (implementation of EU Directive 2019/518, large currency flags)
- E-Receipt solution: Receipt by email to customer and/or dealer email (via QR Code Scan)
- Full OmniChannel functionality through interface to eCommerce systems
- AliPay and WeChat Pay acceptance
- P2PE Certification
- 17 languages, currencies and time zones available

<b>Display</b>	4" colour display 800 x 480 Pixel (WVGA)   Capacitive touchscreen   Integrated signature pad
<b>RAM</b>	512 MB SDRAM, 512 MB Flash (expandable up to 32 GB by micro SD)
<b>Processor</b>	32-bit Cortex A9, 1000 MHz
<b>Dimension</b>	199 x 112 x 53,1 mm   Weight: 400 g
<b>Keypad</b>	Backlit, tactile keyboard EBS-100 compliant, 10 numeric keys, 3 function keys, 1 reset button
<b>Audio</b>	Speaker
<b>External power supply</b>	Input: 100 ~ 240 V AC, 50/60Hz, Output: 5.0 V DC, 2.0 A
<b>Communication/ Interface</b>	LAN, WiFi (2,4 GHz + 5 GHz), RS232, USB, Bluetooth (incl. Beacon Technology), 3 SAM
<b>Card reader</b>	Contactless reader: ISO 14443 A/B, MIFARE, girocard contactless, Mastercard contactless, Visa contactless, American Express contactless, Diners contactless, UPI contactless Chip card reader: EMV L1 & L2 Magnetic stripe reader: 3 track, bidirectional Camera (prepared) : e.g. for reading 1D & 2D codes
<b>Ambient conditions</b>	Operating temp.: 0°C – 50°C, Storage temp.: -20°C – 70°C 5% - 95% relative air humidity, non-condensing
<b>Cash register protocol</b>	ZVT, O.P.I.
<b>Certifications</b>	Compatible with the current specifications DK TA7.2/DC POS 3.0, EMV, RoHS, CE, PCI PTS 6.x, P2PE (on request)