



# CCV Edge IM15

Unattended self-service payment terminal for contactless payments



**PIN on glass** | prevents consumers from 'can't pay situations' as it enables contactless payments with PIN on demand



**Compact** | the all-capabilities terminal design fits even into small machines and into standard cut-outs



**Adaptable** | terminal can be installed flexibly, in landscape or portrait format



**Connectivity** | it connects anywhere with its multiple built-in interfaces and optional 4G interface for remote locations



|                                   |                                                                                                                                                                                                                                                                                                         |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Display</b>                    | 3.5" TFT LCD 480 x 320 Touch Screen   Supports PIN on Glass                                                                                                                                                                                                                                             |
| <b>Card Readers</b>               | Contactless                                                                                                                                                                                                                                                                                             |
| <b>Scanner</b>                    | Reads 1D & 2D codes                                                                                                                                                                                                                                                                                     |
| <b>Memory</b>                     | 512 MB Flash + 512 MB DDR RAM                                                                                                                                                                                                                                                                           |
| <b>Keys / buttons</b>             | 1 x Reset key                                                                                                                                                                                                                                                                                           |
| <b>Audio</b>                      | 1 Speaker                                                                                                                                                                                                                                                                                               |
| <b>Ports</b>                      | 1 x USB Host   1 x USB Device   1 x LAN   1 x RS232   1 x MDB                                                                                                                                                                                                                                           |
| <b>Dimensions</b>                 | 108,4x75x43mm (WxHxD)<br>108,4x75x18,5mm (WxHxD) outside the machine,<br>72x60x24,5mm (WxHxD) within the machine (without cables and mounting accessories)                                                                                                                                              |
| <b>Front plane cutout</b>         | 73 x 61mm, EVA EPS CDM compliant                                                                                                                                                                                                                                                                        |
| <b>Communication / interfaces</b> | WiFi 5 GHz   Bluetooth 5.0   4G RF Modem (optional)                                                                                                                                                                                                                                                     |
| <b>Security</b>                   | 2x SAM                                                                                                                                                                                                                                                                                                  |
| <b>Environmental</b>              | -20°C ~ 70°C (-4°F ~ 158°F) Operating Temperature<br>-30°C ~ 70°C (-22°F ~ 158°F) Storage Temperature<br>5% ~ 95% Relative Humidity, Non-Condensing IP 65   IK09                                                                                                                                        |
| <b>Flammability rating</b>        | V2 according to UL94, IEC 60695-11-10, -20 and IEC 60950-1                                                                                                                                                                                                                                              |
| <b>Certifications</b>             | <b>Payment:</b> EMV Contactless L1   Mastercard payPass L2   Visa payWave L2   American ExpressPay L2   Discover D-PAS L2   Interac_Flash L2   J/Speedy L2   Mastercard TQM   qPBOC L1   qUICS L2  <br><b>Security:</b> PCI PTS 6.x, SRED   CSEC<br><b>Regulatory:</b> FCC   IC   UL   RoHS   CE   UKCA |

All specifications are subject to change and are to be confirmed in the course of the qualification process.